

March, 2008

3M™ Double Coated Splicing Tape 9737

Product Description

3M™ Splicing Tapes 9737 is a high tack, double coated acrylic pressure sensitive adhesives with a polyester carrier.

Product Features

- Versatile splicing tape product meets a wide variety of application requirements.
- Excellent peel, tack and shear.
- Adheres well to Kraft and coated papers.
- Moisture resistant.
- Good temperature resistance.
- Excellent performance at high and low temperatures.



3M™ Double Coated Splicing Tape 9737

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Attribute Modifier
Color	Clear		
Tape Thickness	0.0889 mm	3.5 mil	
Carrier Thickness	0.0127 mm	0.5 mil	
Adhesive Carrier	Polyester		
Liner	55# Densified Kraft Paper		
Liner Color	White		Primary
Liner Thickness	0.081 mm	3.2 mil	

Typical Performance Characteristics

Property	Values		Temp C	Temp F	Substrate	Backing	Notes	Test Condition
180° Peel Adhesion	6.6 N/cm	60 oz/in	23C	73F	Steel	2 mil Aluminum Foil	12 in/min (305 mm/min)	
Minimum Continuous Temperature	-23 °C	-10 °F						
Static Shear	>500 h						1in x 1in	1000 g @ Room Temperature

Relative High Temperature Operating Ranges		Test Condition
149 °C	300 °F	Short Term (minutes, hours)
127 °C	260 °F	Long Term (days, weeks)

Property: Relative High Temperature Operating Ranges

Available Sizes

Please contact your 3M sales representative or contact 3M customer service at 1-800-362-3550 for details on available sizes.

3M™ Double Coated Splicing Tape 9737

Handling/Application Information

Application Techniques

Bond strength is dependent upon the amount of adhesive-to-surface contact. Firm application pressure helps ensure better adhesive contact and improve bond strength.

To obtain optimum adhesion, the bonding surfaces must be clean, dry, and uniform. Some typical surface cleaning solvents are isopropyl alcohol or heptane.* Ideal tape application temperature range is 70°F to 100°F (21°C to 38°C). Initial tape application to surfaces at temperatures below 50°F (10°C) is not recommended because the adhesive becomes too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.

*Note: When using solvents, extinguish all ignition sources, including pilot lights, and follow the manufacturer's precautions and directions for use.

Application Equipment

For additional dispenser information, contact your local 3M sales representative, or the toll free 3M sales assistance number at 1-800-362-3550.

Storage and Shelf Life

Store in original cartons at 70°F (21°C) and 50% relative humidity.

If stored under proper conditions, product retains its performance and properties for 12 months from date of manufacture.

Trademarks

3M is a trademark of 3M Company.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all-3m-products/~/3M-Double-Coated-Tape-9737?N=5002385+3293242576&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=9737

Family Group

	9737	9737R	9738	9738R
Relative High Temperature Operating Ranges (°C) Test Condition: Short Term (minutes, hours)	149	149	149	149
Relative High Temperature Operating Ranges (°C) Test Condition: Long Term (days, weeks)	127	127	127	127
Liner Color Attribute Modifier: Primary	White	White	White	White
Color	Clear	Red	Clear	Red
Tape Thickness (mm)	0.0889	0.0889	0.1092	0.1092

Table continued on next page

Family Group (continued)

	9737	9737R	9738	9738R
Carrier Thickness (mm)	0.0127	0.0127	0.033	0.033
Adhesive Carrier	Polyester	Polyester	Non-Woven Tissue	Non-Woven Tissue
Liner	55# Densified Kraft Paper	55# Densified Kraft Paper	55# Densified Kraft Paper	55# Densified Kraft Paper
Liner Thickness (mm)	0.081	0.081	0.081	0.081

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Recognition/Certification

MSDS: 3M has not prepared MSDS's for these products which are not subject to the MSDS requirements of the Occupational Safety and Health Administration's Hazard Communication Standard, 29 C.F.R. 1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the 3M directions for use, these products should not present a health and safety hazard. However, use or processing of these products in a manner not in accordance with the directions for use may affect their performance and present potential health and safety hazards.

TSCA: These product are not defined as articles under the Toxic Substances Control Act and therefore, are exempt from inventory listing requirements.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



3M United States
3M Center
St. Paul, MN 55144-1000
800-362-3550
www.3M.com

Please recycle.
© 3M 2020. All Rights Reserved.

The brands listed above are trademarks of 3M