

February, 2015

3M™ Adhesive Transfer Tape with Plasticizer Resistant Adhesive F9467U

Product Description

3M™ Adhesive Transfer Tape F9467U is an acrylic pressure sensitive adhesive which has been formulated for bonding to many flexible vinyls and provide outstanding resistance to the effects of plasticizer migration from flexible vinyls.



3M™ Adhesive Transfer Tape with Plasticizer Resistant Adhesive F9467U

General Information

Note: Vinyl formulations differ and plasticizer types and amounts can vary. The most common types of plasticized vinyl contain low molecular weight materials (plasticizers) which tend to migrate out of the vinyl. In the case of adhesive bonding, these plasticizers migrate into the adhesive which can cause softening of the adhesive and loss of bond strength over time.

- The possible effect of plasticizer migration on an adhesive bond can be predicted by accelerated aging for 5 days at elevated temperature (150°F [65°C]). Note: Due to the variability of vinyl formulations, we strongly recommend that the user test each vinyl substrate to determine suitability of the tape for the particular application.
- Natural and synthetic rubber materials such as neoprene and EPDM are also formulated with fillers and plasticizers. Note: 3M™ Adhesive Transfer Tape F-9467U does not resist the effects of these particular fillers and plasticizers and is not recommended for use in bonding these materials.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Attribute Modifier	Notes
Adhesive Thickness	0.089 mm	3.5 mil		
Liner	Polycoated Paper			
Liner Color	Tan		Primary	
Liner Thickness	0.1 mm	4.2 mil		The thickness listed is based on a calculation from manufacturing controlled adhesive coat weights using a density of 1.012 g/cc. While past data pages have listed nominal thicknesses, the coat weight (and theoretical caliper) has not changed.

Typical Performance Characteristics

Property	Values		Test Conditions	Notes	Method	Dwell Time	Dwell Time Units	Temp C	Temp F	Environmental Conditions	Substrate
Static Shear	10000 min		500 g @ Room Temperature	1/2 in x 1 in sample size; Test terminated at 10,000 min							
180° Peel Adhesion	7 N/cm	64 oz/in		12 in/min (300 mm/min)	ASTM D3330	72	hr	22C	72F	52%RH	Stainless Steel

3M™ Adhesive Transfer Tape with Plasticizer Resistant Adhesive F9467U

Available Sizes

Property	Values		Notes
Master Width	1371.6 mm	54 in	More sizes may be available. Please call 800-223-7427 or talk to your local 3M representative for more information.

Environmental Resistance

Bond Build-up: The bond strength of 3M™ Plasticizer Resistant Adhesive increases as a function of time and temperature

Temperature/Heat Resistance: 3M™ Plasticizer Resistant Adhesive is usable for short periods (minutes, hours) at temperatures up to 200°F (94°C) and for intermittent longer periods (days, weeks) up to 160°F (71°C).

Lower Temperature Service Limit: -40°F (-40°C).

UV Resistance: When properly applied, parts are not adversely affected by outdoor exposure.

Handling/Application Information

Application Ideas

- Attaching flexible vinyl graphics to sporting helmets
- Attaching flexible vinyl films and graphics to signs
- Attaching flexible vinyl graphics to vehicles
- Attaching flexible vinyl graphics to collectibles
- Attaching flexible vinyl tubing

Storage and Shelf Life

Store in original cartons at 70°F (21°C) and 50% relative humidity.

When stored under proper conditions, product retains its performance and properties for 24 months from date of manufacture.

Trademarks

3M is a trademark of 3M Company.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all-3m-products/~/3M-Adhesive-Transfer-Tape-F9467?N=5002385+3291148968&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=F9467U

Family Group

	F9465PC	F9467U
Liner Color Attribute Modifier: Primary	Tan, printed	Tan

Table continued on next page

3M™ Adhesive Transfer Tape with Plasticizer Resistant Adhesive F9467U

Family Group (continued)

	F9465PC	F9467U
Adhesive Thickness (mm)	0.13	0.089
Liner	Polycoated Paper	Polycoated Paper
Liner Thickness (mm)	0.1	0.1

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/adhesives. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Recognition/Certification

TSCA: This product is defined as an article under the Toxic Substances Control Act and therefore, it is exempt from inventory listing requirements

MSDS: 3M has not prepared a MSDS for this product which is not subjected to the MSDS requirements of the Occupational Safety and Health Administration's Hazard Communication Standard, 29 C.F.R.1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the 3M directions for use, this product should not present a health and safety hazard. However, use or processing of the product in a manner not in accordance with the directions for use may affect its performance and present potential health and safety hazards.

Note: One of 3M's core values is to respect our social and physical environment. 3M is committed to comply with ever-changing, global, regulatory and consumer environmental, health, and safety (EHS) requirements. As a service to our customers, 3M is providing information on the regulatory status of many 3M products. Further regulation information including that for OSHA, USCPSI, FDA, California Proposition 65, REAY and RoHS, can be found at 3M.com/regs.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

