BW0125-1

1/8" BLACK POLYETHYLENE SINGLE COATED FOAM TAPE

PRODUCT DESCRIPTION


Single Coated Tape with Liner

BW0125-1 is a 1/8" thick black closed cell, crosslinked polyethylene foam coated on one side with a general purpose rubber based adhesive with a white kraft liner.

FEATURES & BENEFITS

- Easily die cut
- High immediate bond
- Great chemical resistance
- Low compression set
- Best conformability, cushioning, & vibration damping

PRODUCT CONSTRUCTION



PRODUCT SPECIFICATIONS

Test	Typical Value		Туј	oical Value (Metric)	Test Method
Product Thickness (Total)	126.80	mils	3,221	mm	PSTC-133
Adhesive Thickness	1.80	mils	0.046	mm	PSTC-133
Carrier Thickness	125.00	mils	3.175	mm	PSTC-133
Peel Adhesion	75	oz/in	20.84	N/25mm	PSTC-101
Tack	33	oz	936	g	ASTM D 2979
Shear Adhesion	>24	hrs @ 2.2 psi	>24	hrs @15.2 kPa	PSTC-107
Tensile Strength	160	lb/in	700	N/25mm	PSTC-131
Elongation	210	%	210	%	
Minimum Service Temperature	50	°F	10	°C	
Maximum Service Temperature	155	°F	68	°C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street Easthampton, MA 01027

413-527-7120 Main 800-356-3572 Toll Free U.S.

www.adhesiveapps.com



