



Product Information

Cactus® Double Coated Tissue Tape F2480 is an acrylic solvent based adhesive tape that offers a high grab adhesive system that provides quick laminating results at a wide temperature range, chemical and UV resistance.

Composition & Physical Properties

Adhesive System	: Solvent Acrylic	Tape Thickness	: 3.1 mil (0.08 ± 0.005 mm)
Carrier	: Tissue	Loop Tack FINAT-9	: 52.8 oz/inch (1.5kg/25mm)
Liner Thickness	: 5 mil	Peel Adhesion PSTC-3	: 49.28 oz/inch (1.4kg/25mm)
Liner Material	: Bleached Kraft Paper	Shear Strength PSTC-7	: Over 24 hrs with 35.2 oz loading on 1" x 1" (1.0kg/25mm x 25mm)
Liner Density	: #74 (110 g/m ²)	Heat Resistance	: Over 24 hrs with 17.6 oz loading on 25mm x 25mm at 176°F (80°C)
Liner Color	: White	Service Temperature	: -22°F ~ 212°F (-30°C ~ 100°C)
Tape Color	: White		

Applications

- Fastening to smooth surface objects such as metal plates, film and plastic parts with high conformity.
- Fixing and laminating of various substrates of electronic components and devices.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.