TECHNICAL DATA SHEET

MED 6000

Double-Coated Film


MED 6000 is a double-coated, conformable, transparent polyethylene film with an acrylic adhesive on both sides. This product is designed to adhere to many foams, films and nonwovens and has a heavy-weight liner, allowing for greater flexibility in product design and converting processes.

TYPICAL APPLICATION

Designed for mounting medical devices and manufacturing surgical drapes.

FEATURES AND BENEFITS

- Conformable
- Moisture resistant
- Transparent
- Die-cuttable
- Gamma and EtO sterilizable



Product Construction						
	TYPICAL VALUES*		DESCRIPTION			
UNWIND ADHESIVE THICKNESS	2.0 mils	50 µm	Acrylic adhesive designed for medical applications			
CARRIER THICKNESS	3.0 mils	75 µm	Transparent polyethylene film			
LINER ADHESIVE THICKNESS	1.3 mils	35 µm	Acrylic adhesive designed for medical applications			
LINER THICKNESS	4.4 mils	110 µm	White double-coated kraft			



^{*}Refer to product specifications for material acceptance limits.

MED 6000

Double-Coated Film

Physical Properties [Not intended as a specification]						
	TEST METHOD*	TYPICAL VALUES†				
PEEL ADHESION ON POLYETHYLENE (PE) - LINER	TDS-01	0.6 lbf/in	2.6 N/25 mm			
PEEL ADHESION ON POLYETHYLENE (PE) - UNWIND	TDS-01	0.8 lbf/in	3.5 N/25 mm			
PEEL ADHESION ON STAINLESS STEEL (SS) - LINER	TDS-03	4.8 lbf/in	21.0 N/25 mm			
PEEL ADHESION ON STAINLESS STEEL (SS) - UNWIND	TDS-03	6 lbf/in	26.5 N/25 mm			
LINER RELEASE	TDS-06	1.2 oz/in	35 g/25 mm			
FINAT TACK - LINER	TDS-07	4.0 lbf/in	17 N/25 mm			
FINAT TACK - UNWIND	TDS-07	4.3 lbf/in	19 N/25 mm			
DYNAMIC SHEAR - LINER	TDS-10	15 lbf/in	60 N/25 mm			
DYNAMIC SHEAR - UNWIND	TDS-10	15 lbf/in	60 N/25 mm			
ELONGATION						
MACHINE DIRECTION	TDS-15	500%				
CROSS DIRECTION	TDS-15	800%				
LOAD AT BREAK						
MACHINE DIRECTION	TDS-15	11 lbf/in	50 N/25 mm			
CROSS DIRECTION	TDS-15	9 lbf/in	40 N/25 mm			

^{*}Test method information available upon request.

STORAGE AND SHELF LIFE: Two years when stored at 23°C (73°F), 50% relative humidity, out of direct sunlight, in original packaging.

DEFINITIONS: "Avery Dennison Medical" means Avery Dennison Corporation. "Purchaser", "Customer" and/or "User" means the customer of Seller, jointly referred to as "Parties" or individually as "Party". For the purpose of these Conditions, "Products" means goods, all parts, components and services sold by Avery Dennison Medical to Purchaser.

SAFETY: Customers/Users have full responsibility to determine the suitability of Avery Dennison Medical products for applications in their businesses. This includes both safety and biocompatibility assessments. Material Safety Data Sheets (MSDS) will be provided upon request, as well as summaries of components' biocompatibility testing results (ISO 10993), where available. Customers should perform their own assessments on final products in compliance with applicable regulatory requirements.

LIMITED WARRANTY: All statements, technical information and recommendations concerning Products sold or samples provided by Avery Dennison Medical are based upon tests believed to be reliable but do not constitute a guarantee or warranty, and the Purchaser is responsible for determining whether a Product is fit for a particular purpose and for the Product's application. All Products are sold and samples of products are provided with the understanding that the Purchaser has independently determined the suitability of such products for its purposes. Avery Dennison Medical warrants the Products to be free from defects in material and workmanship by the time of the delivery (in other words: the initial date of the shipment). Should any failure to conform to this warranty appear (i) during the time period stated on the specific product specification sheet, or (ii) during the time period on the specific product information literature in effect at time of shipment, or (iii) if not otherwise specified then within one year after the initial date of shipment, then Avery Dennison Medical shall, upon notification thereof and substantiation that the Products have been stored and applied in accordance with the standards set by Avery Dennison Medical, correct such defects without charge to the Purchaser by either suitable repair or replacement in its sole discretion of Avery Dennison Medical at the Avery Dennison Medical plant or at the location of the Products. Such price of repair or replacement shall not exceed the purchase price of the Products upon which the liability is based, and Avery Dennison Medical may in its sole discretion refund the purchase price of the Product in lieu of any repair or replacement. For Customers, all Avery Dennison Medical materials/products described herein are sold subject to the Conditions of Sales to be found on https://medical.averydennison.com/en/home/terms-and-conditions.html, which may be updated from time to time by Avery Dennison and of which a copy is also available on request. This

LIMITATION OF LIABILITY: In no event shall Avery Dennison Medical be liable for any incidental or consequential damages, including but not limited to, loss of profit, loss of use of production or loss of capital. The remedies of the Purchaser set forth herein are exclusive and the total liability of Avery Dennison Medical with respect to any contract, or anything done in connection therewith such as the performance or breach hereof, or from the manufacture, sale, delivery, resale, installation or use of products whether arising out of contract, negligence, strict liability, tort or any other legal theory or under any warranty, or otherwise, shall not exceed the purchase price of the products upon which the liability is based.

To learn more about how our material and adhesive science expertise can help drive your next innovation, call us

US: +1 440 534 2600 Belgium: +32 14 40 48 11 Ireland: +353 43 3349586

www.medical.averydennison.com



[†]Refer to product specifications for material acceptance limits.