



**Cactus® Double Coated Film Tape**

**Technical Data Sheet No. P2970**

**Product Information**

Cactus® Double Coated Film Tape P2970 is a solvent-based acrylic pressure sensitive adhesive tape which offers high initial tack for quick bonding results. Ideal for general purpose industrial applications such as bonding, fixing, mounting, and splicing.

**Composition & Physical Properties**

Adhesive System	: Solvent Acrylic	Tape Thickness	: 3.5 mil (0.09 ± 0.005 mm)
Carrier	: 1/2 mil PET Film	Tack	: J. Dow No. 20
Liner Thickness	: 4.7 mil	Peel Adhesion	: PSTC-3 42.3 oz/in (1.2kgs/25mm)
Liner Material	: Polycoated Kraft Paper	Shear Strength PSTC-7	: Over 24 hrs with 35.2 oz loading on 1" x 1" (1.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Density	: #74 (110 g/m <sup>2</sup> )	Service Temperature	: -4°F ~ 144°F (-20°C ~ 80°C)
Liner Color	: White		
Tape Color	: Clear		

**Applications**

- For general industrial applications, such as bonding, fixing, mounting and splicing.
- Mounting of nameplates, trophies and signs.
- Temporary bonding of insulation materials (as an assembly aid) in construction industry.
- Ideal for stationery industry

**Disclaimer and Limitation of Liability**

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.