DermaMed Coatings Company, LLC

DM-2065

Single Coated Woven Fabric

Product Data Sheet

CONTENTS

Face	Cotton/viscose fabric
Adhesive	Latex-free, medical rubber pressure-sensitive
Backing	Silicone coated one-side, 54 lb basis weight

FACE PROPERTIES

Basis Weight	270 g/m^2

Typical substrate values of uncoated materials.

ADHESIVE PROPERTIES

Peel Adhesion		>1000 g/in
2 mil PET	Test Method:	DMT-PSTC-1 HDPE Panels
Peel Adhesion		>5000 g/in
2 mil PET	Test Method:	DMT-PSTC-1 SS Panels

Destructive test. Refer to the HDPE spec above

Shelf Life	TBD
Thickness	4.5 mil
Color	White

The base adhesive passes Cytotoxicity, however the zinc load used to pigment the adhesive causes the product to fail, due to the nature of zinc. The ZnO is USP grade. Justification for this occurrence is available upon request.

Biocompatibility	Cytotoxicity	Pass
	Primary Dermal	Pass
	Buehler	Pass

PRODUCT DESCRIPTION

DM-2065 is a beige, elastic woven fabric tape. It is coated on one side with a white, medical rubber-based adhesive and supplied on a paper liner.

SPLICES

Splices on tape and liner are functional in that they are intended for continuous process conditions.

STANDARD LABELING

Materials will have core labeling stating the part number, roll number, lot number, width, and linear feet per roll. *Note: Any additional labeling requirements should be noted at time of order entry.*

TRACEABILITY

Material traceability must comply with current Good Manufacturing Practices. Each shipment of material will contain a lot number, which is traceable through production records. Certificate of Conformance will accompany each shipment.

STORAGE CONDITIONS

Store in original protective packaging at temperatures between 50-80°F and 40-60% RH.

APPEARANCE

Virtually free from foreign and dark colored matter.

ROLL DIMENSIONS

Smaller roll length by request.

Length	600	linear feet max.
Width	58	inch max.
Core	3	inch inside diameter

Issue Date:	May 4, 2004
Revision Date:	December 1, 2015

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability and fitness for use. All users of the material are responsible for assuring that it is suitable for their needs, environment, and end use. Typical values are not intended to be used for specification development. All data is subject to change, as DermaMed deems appropriate.

381 Geneva Avenue * Tallmadge, OH 44278
271 Progress Boulevard * Kent, OH 44240
Tel:330-633-8216 * Fax: 330-633-2461

CONFIDENTIAL

UNCONTROLLED COPY