



TTL-2331 ***2 MIL BOPP FILM CARTON SEALING TAPE***

APPLICATIONS

TTL-2331 features a biaxially oriented polypropylene (BOPP) film backing coated with a water based acrylic adhesive system. Designed for economical packaging, sealing applications. Recommended for sealing cartons that weight up to 40 lbs. Suitable for use with hand dispensers and machine dispensing carton sealing machines.

FEATURES/BENEFITS

- Economical polypropylene film provides good strength for light-medium duty package sealing.
- All-Weather acrylic adhesive features good shear strength and long shelf life.
- Clear BOPP film and emulsion acrylic adhesive provide excellent clarity.
- Also available in custom E-Commerce Return Strips.

TECHNICAL DATA

Adhesive	: Emulsion Acrylic
Backing	: 28μ Biaxially Oriented Polypropylene Film
Color	: Clear, Tan
Total Tape Thickness	: 2.0 mils (0.050mm)
Elongation	: 180%
Tensile Strength	: 18 lbs/inch of width
Adhesion to Steel	: 22 oz/inch of width
Temperature Range	: 14°F to 158°F
Application Temperature	: 32°F to 140°F
Standard Lengths	: 55 yards, 110 yards, 1000 yards

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.